DESCRIPTIONS

350W， AC-DC Open Frame Power Supply



RoHS

5 Years Warranty

c UL us Report UL62368-1 UL60601-1

CE Report EN62368-1

UKCA Report BS EN62368-1

FEATURES

- Universal 90 - 264VAC or 127 - 370VDC input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range: -40℃ to +70℃
- Built-in active PFC function
- High I/O isolation test voltage up to 4000VAC
- Extremely low leakage current < 0.1mA
- Stand-by power consumption < 1.0W
- The base plate with conformal coating
- Output short circuit, over-current, over-voltage protection, over-temperature protection
- Installing in system of Safety Class I (with PE), Class II (no PE) is available
- Suitable for BF application
- Operating altitude up to 5000m
- Safety according to GB4943, IEC60335, IEC/EN60601

APPLICATIONS

- Industrial
- LED
- Street light contro
- Electricity
- Security
- Telecommunications
- Smart home
- Medical

Selection Guide

Certification	Part No.*	Cooling method	Output Power* (W)	Nominal Output Voltage and Current (Vo/Io)	Output adj. Range (V)	Efficiency at 230VAC (%) Typ.*	Max. Capacitive Load (μF)
UL/EN/BS EN	AOF350-2B-12-C	Air cooling	180	12V/15A	11.4-12.6	92	6000
		20.5CFM	300	12V/25A			
UL	AOF350-2B-15-C	Air cooling	180	15V/12A	14.25-15.75	92	5000
		20.5CFM	325	15V/21.67A			
--	AOF350-2B-19-C	Air cooling	180.5	19V/9.5A	17.1-19.9	92.5	4000
		20.5CFM	324.9	19V/17.1A			

UL/EN/BS EN	AOF350-2B-24-C	Air cooling	199.9	24V/8.33A	22.8-25.2	93	3200
		20.5CFM	350.4	24V/14.6A			
EN/BS EN	AOF350-2B-27-C	Air cooling	199.8	27V/7.4A	25.65-28.35	93	2600
		20.5CFM	351	27V/13A			
	AOF350-2B-36-C	Air cooling	200.16	36V/5.56A	34.2-37.8	93	2000
		20.5CFM	350.28	36V/9.73A			
	AOF350-2B-48-C	Air cooling	200.1	48V/4.17A	45.6-50.4	94	2000
		20.5CFM	350.4	48V/7.3A			
	AOF350-2B-54-C	Air cooling	199.8	54V/3.7A	51.3-56.7	94	2000
		20.5CFM	351	54V/6.5A			

Notes: 1.*Under any conditions, the total power of the product should not exceed the rated power. When the output voltage is increased, the total output power cannot exceed the rated output power, when the output voltage is decreased, the output current cannot exceed the rated output current;
2.*When measuring the full load efficiency, the fan should be connected to an external power supply. Fan loss is not included in the input power;
3.*AOF-C Products without shell is also available, named AOF350-2B-xx.
4.*The product picture is for reference only, for details, please refer to the actual product.

Specifications

Product Specifications	Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input Specifications	Input Voltage Range	AC input		90	--	264	VAC
		DC input		127	--	370	VDC
	Input Voltage Frequency			47	--	63	Hz
	Input Current	115VAC		--	--	4	A
		230VAC		--	--	2	
	Inrush Current	115VAC	Cold start	--	50	--	
		230VAC		--	75	--	
	Power Factor	115VAC	Full load	0.98	--	--	--
		230VAC		0.95	--	--	
	Leakage Current	240VAC		<0.1mA; Single fault <0.5mA			
	Hot Plug			Unavailable			
Output Specifications	Output Voltage Accuracy*	Full load range	12V/15V/19V	--	±3	--	%
			24V/27V/36V/48V/54V	--	±2	--	
	Line Regulation	Rated load		--	±0.5	--	
	Load Regulation	0% - 100% load		--	±1	--	%
	Output Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	12V	--	--	120	mV
			15V	--	--		
			19V	--	--		
			24V	--	--	150	
			27V	--	--	200	
			36V	--	--		
			48V	--	--	250	
			54V	--	--		
	Temperature Coefficient			--	±0.03	--	%/℃
	Minimum Load			0	--	--	%
	Hold-up Time	230VAC, full	Free air convection	12	14	--	ms

		load	20.5CFM	6	8	--	
	Stand-by Power Consumption	230VAC		--	--	1.0	W
	Short Circuit Protection	recover time <5s after the short circuit disappear		Hiccup, continuous, self-recover			
	Over-current Protection			≥110%Io, self-recover			
	Over-voltage Protection	12V		≤15.0V	Output voltage turn off, re-power on for recover		
		15V		≤18.5V			
		24V		≤30.0V			
		27V		≤33.5V			
		36V		≤45.0V			
		48V		≤59.5V			
		54V		≤63.0V			
	Over-temperature Protection*			Output voltage turn off, re-power on for recover after the temperature drops.			
	Fan power *	12V/15V/24V/36V/48V/54V		Offer output power of 12V/0.5A with output voltage accuracy ±15%			
		19V		Offer output power of 12V/0.5A with output voltage accuracy -15% - +25%			
		27V		Offer output power of 12V/0.5A with output voltage accuracy -25% - +15%			
General Specifications	Isolation Test	Input - ⏚	Electric Strength Test for 1min., leakage current <10mA	2000	--	--	VAC
		Input- output		4000	--	--	
		Output - ⏚		1500	--	--	
	Insulation Resistance	Input - ⏚	Environment temperature: 25±5℃, Relative humidity: <95%RH, non-condensing Testing voltage: 500VDC	100	--	--	MΩ
		Input - output		100	--	--	
		Output - ⏚		100	--	--	
	Operating Temperature			-40	--	+70	℃
	Storage Temperature			-40	--	+85	
	Storage Humidity	Non-condensing		10	--	95	%RH
	Operating Humidity			20	--	90	
	Power Derating	Operating temperature derating	+50℃ to +70℃	2.5	--	--	%/℃
			-40℃ to +50℃	0	--	--	
		Input voltage derating	90VAC - 100VAC	1.0	--	--	%/VAC
			100VAC - 264VAC	0	--	--	
	Safety Class			CLASS I (with PE and must be connected)/CLASS II (without PE)			
	Isolation level	Input - output		2 × MOPP			
		Input - ⏚		1 × MOPP			
		Output - ⏚		1 × MOPP			
	MTBF	MIL-HDBK-217F@25℃		> 300,000 h			
Mechanical	Case Material	Metal (AL5052+SUS304)					
	Dimensions	130.0mm × 86.0mm × 35.0 mm					

Specifications	Weight	430g (Typ.)
	Cooling Method*	Free air convection (180W/200W) / 20.5CFM (300W/325W/350W)

Notes: 1. * Output Voltage Accuracy: including setting error, line regulation, load regulation.

2.* The "Tip and barrel method" is used for ripple and noise test, output parallel 10uF electrolytic capacitor and 0.1uF ceramic capacitor,

3.* When the product works under light load (≤10%Io), in order to improve efficiency, the value of ripple & noise will be 1.5 times of the full load specification;

4.*For fan power connection method, please refer to pin 6, 7 of the dimension drawing.

5.*Please refer to the product characteristic curve for cooling method and power derating.

Electromagnetic Compatibility (EMC)

Electromagnetic Compatibility (EMC)	Emissions (EMI)	CE	CISPR32/EN55032 CLASS B	
		RE	CISPR32/EN55032 CLASS B (Category I, CLASS B; Category II, CLASS A)	
		Harmonic Current	IEC/EN61000-3-2 CLASS A and CLASS D	
		Flicker	IEC/EN61000-3-3	
	Immunity (EMS)	ESD	IEC/EN 61000-4-2 Contact ±8KV/Air ±15KV	perf. Criteria A
		RS	IEC/EN 61000-4-3 10V/m	perf. Criteria A
		EFT	IEC/EN 61000-4-4 ±4KV	perf. Criteria A
		Surge	IEC/EN 61000-4-5 ±2KV/±4KV	perf. Criteria A
		CS	IEC/EN61000-4-6 10 Vr.m.s	perf. Criteria A
		DIP	IEC/EN61000-4-11 0%, 70%	perf. Criteria B

Notes: 1.*The power supply is considerated a component as part of system, all EMC items are tested on a metal plate (L x W x H, 360mm x 360mm x 1mm). Power supply should be combined with final equipment for EMC confirmation;

2.*Category I products with PE, which must be connected, category II products without PE.

3.*perf. Criteria:


A: The equipment shall continue to operate as intended without operator intervention;

B: After the test, the equipment shall continue to operate as intended without operator intervention;


C: Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions.

Characteristic Curve

12V-C (full load 300W with Forced Air)





15/19V-C (full load 325W with Forced Air)



24/27/36/48/54V-C (full load 350W with Forced Air)


AOF350-2B-xx-C Input Voltage Derating Curve







Note: 1.With an AC input voltage between 90 - 100VAC and a DC input between 127 - 140VDC the output power must be derated as per the temperature derating curves.

2. This product is suitable for applications using natural air cooling.






Dimensions and Recommended



THIRD ANGLE PROJECTION

Pin-Out			
Pin	Mark	Product Connector	Customer Connector
1	AC(N)/DC-	JST B5P-VH or equivalent	Housing: JST VHR Contact: JST SVH-21T-P1.1 or CPJ-018
2	NC		
3	AC(L)/DC+		
4	NC		
5	⏚		
6	FAN-	KANGDAO 2.5XHS-2A or equivalent	Housing: KANGDAO 2.5XHS-2Y Contact: KANGDAO 2.5XH-TE or CPJ-008
7	FAN+		
8	-Vo		
9	+Vo		
	ADJ	Output adjustable resistor	

Position	Screw Spec.	L(max)	Torque(max)
①－②	M3	4mm	0.4N·m
③－⑥	M3	3mm	0.4N·m



Note:
1. Unit: mm[inch]
2. ADJ: Output adjustable resistor
3. General tolerances: ± 1.00[± 0.039]
4. Connector tightening torque: M3.5, 0.8N·m
5. Wire range: 18-14AWG
6. The layout of the device is for reference only, please refer to the actual product

CAUTION: Double pole, neutral fusing. Disconnect mains before servicing.

ATTENTION. Double pôle/fusible sur le neutre. Débrancher l'alimentation avant l'entretien.

Note:

1. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25℃, humidity<75%RH with nominal input voltage and rated output load;
2. The ambient temperature derating of 5℃/1000m is needed for operating altitude greater than 2000m;
3. All index testing methods in this datasheet are based on our company corporate standards;
4. In order to improve the efficiency at light load, there will be audible noise generated, but it does not affect product performance and reliability;
5. We can provide product customization service, please contact our technicians directly for specific information;
6. Products are related to laws and regulations: see "Features" and "EMC";
7. The out case needs to be connected to PE (⏚) of system when the terminal equipment in operating;
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units;
9. The power supply is considered a component which will be installed into a final equipment. All EMC tests should be confirmed with the final equipment.
10. The image certification marks are for reference only; please refer to the selection table for actual specifications. Certification is based on the physical mark or packaging label.