Descriptions

1W isolated DC-DC converter



RoHS

3 Years Warranty

c UL us UL62368-1

CE Report EN62368-1

UKCA Report BS EN62368-1

Features

- Continuous short-circuit protection
- No-load input current as low as 8mA
- Operating ambient temperature range: -40℃ to +85℃
- High efficiency up to 75%
- I/O isolation test voltage 1.5k VDC

Applications

- Industrial control
- power
- home appliances
- Instrumentation
- Communication
- Civil applications

Selection Guide

Certification	Part No.	Input Voltage (VDC)	Output		Full Load Efficiency (%)	Capacitive Load (μF)
		Nominal (Range)	Voltage (VDC)	Current (mA) Max./Min.	Min./Typ.	Max.
EN/BS EN	DFLS1-IB0503	5 (4.75-5.25)	3.3	250/25	63/67	2400
UL/EN/BS EN	DFLS1-IB0505		5	200/20	66/70	2400
EN/BS EN	DFLS1-IB0509		9	111/12	67/71	1000
UL/EN/BS EN	DFLS1-IB0512		12	84/9	68/72	560
EN/BS EN	DFLS1-IB0515		15	67/7	69/73	560
	DFLS1-IB0524		24	41/4	69/73	100
UL/EN/BS EN	DFLS1-IB1205	12 (11.4-12.6)	5	200/20	69/73	2400
EN/BS EN	DFLS1-IB1209		9	111/12	69/73	1000
	DFLS1-IB1212		12	83/9	69/73	560
	DFLS1-IB1215		15	67/7	71/75	560
	DFLS1-IB2403	24 (22.8-25.2)	3.3	250/25	65/71	2400
	DFLS1-IB2405		5	200/20	67/73	2400
	DFLS1-IB2409		9	111/12	67/73	1000
	DFLS1-IB2412		12	83/9	67/73	560
	DFLS1-IB2415		15	67/7	67/73	560

Specifications

Product Specifications	Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input Specifications	Input Current (full load / no-load)	5V input	3.3/5VDC output	--	286/8	303/--	mA
			9/12VDC output	--	282/12	299/--	
			15/24VDC output	--	274/18	290/--	
		12V input	5/9/12VDC output	--	115/8	121/--	
			15VDC output	--	112/8	118/--	
		24V input	3.3VDC output	--	59/8	65/--	
			5/9/12/15VDC output	--	58/8	63/--	
	Reflected Ripple Current			--	15	--	
	Input Filter			Capacitor Filter			
	Hot Plug			Unavailable			
Output Specifications	Voltage Accuracy			--	--	±3	%
	Linear Regulation	Input voltage change: ±1%		--	--	±0.25	
	Load Regulation	10%-100% load	3.3VDC output	--	--	±3	
			Other output	--	--	±2	
	Ripple & Noise*	20MHz bandwidth 5VDC input	Other output	--	30	75	mVp-p
			24V output	--	50	100	
		20MHz bandwidth 12/24VDC input	3.3/5/9/12VDC output	--	30	100	
			15VDC output	--	80	150	
	Temperature Coefficient	100% load		--	±0.02	--	%/℃
	Short-circuit Protection			Continuous, self-recovery			
General Specifications	Isolation	Input-output electric strength test for 1 minute with a leakage current of 1mA max.		1500	--	--	VDC
	Insulation Resistance	Input-output resistance at 500VDC		1000	--	--	MΩ
	Isolation Capacitance	Input-output capacitance at 100kHz/0.1V		--	20	--	pF
	Operating Temperature	Derating when operating temperature≥ 71℃ (see Fig.1)		-40	--	85	℃
	Storage Temperature			-55	--	125	
	Case Temperature Rise	Ta=25℃	3.3VDC input	--	30	--	
			Other input	--	25	--	
	Pin Soldering Resistance Temperature	Soldering spot is 1.5mm away from case for 10 seconds		--	--	300	
	Storage Humidity	Non-condensing		5	--	95	%RH
	Vibration			10-150Hz, 5G, 30 Min. along X, Y and Z			
	Switching Frequency	100% load,	5VDC input	--	270	--	kHz

		nominal input voltage	12/24VDC input	--	260	--	
	MTBF	MIL-HDBK-217F@25℃		3500	--	--	k hours
Mechanical Specifications	Case Material	Black plastic; flame-retardant and heat-resistant (UL94V-0)					
	Dimensions	19.65 x 6.00 x 10.16mm					
	Weight	2.1g(Typ.)					
	Cooling Method	Free air convection					
Note: * The "parallel cable" method is used for Ripple and Noise test.							

Electromagnetic Compatibility (EMC)

Emissions	CE	CISPR32/EN55032 CLASS B
	RE	CISPR32/EN55032 CLASS B
	ESD	IEC/EN61000-4-2 Air ±8kV, Contact ±6kV perf. Criteria B
Note: Refer to Fig. 4 for recommended circuit test.		

Characteristic Curve






Fig. 1








Fig. 2

Design Reference

1. Typical application




Fig. 3

Vin	Cin	Vo	Cout
5VDC	4.7μF/16V	3.3VDC/5VDC	10μF/16V
12VDC	2.2μF/25V	9VDC	2.2μF/16V
24VDC	1μF/50V	12VDC	2.2μF/25V
--	--	15VDC	1μF/25V

2. EMC compliance recommended circuit






Fig 4


Input voltage		5DVC		12/24DVC
Output voltage		3.3/5/9VDC	12/15/24VDC	--
Emissions	C1/C2	4.7μF /50V	4.7μF /50V	4.7μF /50V
	CY	100pF	1000pF	270pF /2kV
	C3	Refer to the Cout in table 1		
	LDM	6.8μH		

Dimensions and Recommended





Note: Grid 2.54*2.54mm



Note:
Unit: mm[inch]
Pin section tolerances: ± 0.10[± 0.004]
General tolerances: ± 0.25[± 0.010]

Pin–Out	
Pin	Mark
1	Vin
2	GND
4	0V
6	+Vo

Notes:

1. If the product is not operated within the required load range, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
2. The maximum capacitive load offered were tested at input voltage range and full load;
3. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25℃, humidity<75%RH with nominal input voltage and rated output load;
4. All index testing methods in this datasheet are based on our company corporate standards;
5. Products are related to laws and regulations: see "Features" and "EMC"
6. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.